Accessories

Power supply



A power supply is available for 24 V and zero pressure accumulation 400 V $\,$ conveyors. The power supply units are installed in a robust cabinet, and each power supply has a main switch and internal fuse.

Designation	Dimensions	Reference number
Power supply 24 V/20 A	380 x 380 x 211 mm	1015147
Power supply 24 V/40 A	380 x 380 x 211 mm	1015148

Sensor kit



Sensors detect materials on the conveyors and determine their position. Reflex light barriers are used, which require a reflecting mirror (reflector) on the opposite side of the light barrier in order to return the light beam. The sensor kit consists of the sensor and the matching plastic housing, including

fastening clip. The housing can be attached directly to the roller conveyor or to a universal support.

Designation	Dimensions	Reference number
Sensor kit	43 x 26 x 18 mm (L x W x H) (H 26 mm with studs)	63010249

Reflector kit



	.
Designation	Dimensions
Reflector kit	54 x 18 x 30 mm (L x W x
Kellector kli	`
	(H 39 mm with studs)

Universal support, fixed





Designation

Universal support, fixed

		Dimensions
--	--	------------

The reflector kit returns the light beam back to the sensor. The kit includes a fastening clip and can be attached directly to the roller conveyor or to an universal support.

Reference number

x H)

64000905

Side guides, sensors, reflectors and other add-on components, such as scanners, are attached to the fixed universal support.

Fixed universal supports are attached directly to the side profile.Sensor holder

Reference number

60 mm (55 mm above T.O.R.)

1015014