

TC2B

series



Product Segments

Comfort Motion

General Features

Number of motors

Max. output

Input Voltage

Built-in transformer type

Certificate

Plug support

Color

Over current protection

1~3

32V DC, 6.25A

100, 120, 230V AC, or 100~240V AC

(SMPS)

SMPS

EMC


EU, USA, AUS, UK, or JPN


Black or grey

TC2B Series

Drawing

Standard Dimensions (mm)







TC2B Ordering Key



TC2B

)				Version: 2091211-J
Input voltage	1 = 100V AC	2 = 120V AC	3 = 230V AC	4 = 100~240V AC (SMPS)
Plug	1 = EU	3 = AU	5 = JP	
	2 = US	4 = UK		
Number of Actuators	1 = 1	2 = 2	3 = 3	
Color	1 = Black	2 = Grey (Pantone 428C)		
Cable Length (mm)	1 = Straight, 2000	2 = Straight, 4000		
Fixation	1 = On actuator (accessories: fixing screws*1)		2 = On iron frame (accessories: mounting brackets & screws)	
Backup Battery	0 = Without 1 = Without battery, with a connection cable		2 = With 2*9V batteries	
Transformer	4 = SMPS (SPM-58, 2A)			
MCU	0 = Without	1 = With		
Wireless Control	0 = Without	R = RF (315 MHz) For NA	F = RF (433 MHz) For EU	H = IR
IP Rating	1 = Without	2 = IP54		

Terms of Use