

Archive mobil shelving for low weight storage.



100% more space on the same footprint.

Space-saving mobile shelving makes efficient use of storage space in stockrooms and warehouses.

Compared to static shelving, the elegant move mobile shelving system enables twice the number of shelving units to be installed on the same footprint. Storage capacity is therefore increased by nearly 100%. This often enables you to avoid renting additional storage space.

Details

- Space-saving mobile shelving system to store cartons and tools as well as small items in semi-open storage boxes or transport bins on galvanised shelves (25 mm canted edges), height-adjustable in increments of 25 mm.
- 3 heights: 1715 mm, 2040 mm, 2340 mm. Variable overall length (see table for ready-configured models), incl. service aisle with minimum width of 750 mm.
- bay width 1000 mm, overall width: 1200 mm.
- Rigidity provided by in-bay diagonal bracing.
- Shelving units operated using standard hand-wheels. Hand-rail or electric-powered operation options on request.
- Units travel smoothly on integrated platform, optional: can be locked as a closed-off block.
- Fronts available in a range of options. Standard: sheet steel panels in RAL 7035 light-grey finish (other colours available as optional extras, see page 202), optionally in perforated metal or sound-proofed finishes.



The shelving platform rests solidly on the flooring without additional bracing. Here the straight-edged version.



Alternative: shelving platform with chamfered edging (on request).




Galvanised shelves.

elegant move Mobile Shelving System (non-lockable), RAL 7035 light-grey (galvanised shelves)

specification

4 binder height units = 4 BHU
height 1715 mm
bay load 500 kg




installation length 2700 mm




3 x 2-sided

3400 mm



4 x 2-sided

4100 mm



5 x 2-sided

4800 mm



6 x 2-sided

bay depth 600 mm/usable depth 2 x 300 mm

model

linear storage metres

emz4-3

24

emz4-4

32

emz4-5

40


emz4-6

48

price in €

specification

5 binder height units = 5 BHU
height 2040 mm
bay load 500 kg



installation length 2700 mm



3 x 2-sided

3400 mm



4 x 2-sided

4100 mm



5 x 2-sided

4800 mm



6 x 2-sided

bay depth 600 mm/usable depth 2 x 300 mm

model

linear storage metres

emz5-3

30

emz5-4

40

emz5-5

50


emz5-6

60

price in €

specification

6 binder height units = 6 BHU
height 2340 mm
bay load 500 kg



installation length 2700 mm



3 x 2-sided

3400 mm




4 x 2-sided

4100 mm



5 x 2-sided

4800 mm



6 x 2-sided

bay depth 600 mm/usable depth 2 x 300 mm

model

linear storage metres

emz6-3

36

emz6-4

48

emz6-5

60

emz6-6


72

price in €

elegant move Mobile Shelving System (lockable), RAL 7035 light-grey (galvanised shelves)

specification

4 binder height units = 4 BHU
height 1715 mm
bay load 500 kg



installation length 3000 mm




2 x 1-sided

3600 mm




2 x 1-sided

4200 mm



2 x 1-sided

4800 mm



2 x 1-sided

bay depth 300 & 600 mm/usable depth in each case 350 mm

model

linear storage metres

emvz4-22

24

emvz4-32

32

emvz4-42

40


emvz4-52

48

price in €

specification

5 binder height units = 5 BHU
height 2040 mm
bay load 500 kg




installation length 3000 mm




2 x 1-sided

3600 mm




2 x 1-sided

4200 mm



2 x 1-sided

4800 mm



2 x 1-sided

bay depth 300 & 600 mm/usable depth in each case 350 mm

model

linear storage metres

emvz5-22

30

emvz5-32

40

emvz5-42

50


emvz5-52

60

price in €

specification

6 binder height units = 6 BHU
height 2340 mm
bay load 500 kg



installation length 3000 mm




2 x 1-sided

3600 mm




2 x 1-sided

4200 mm



2 x 1-sided

4800 mm



2 x 1-sided

bay depth 300 & 600 mm/usable depth in each case 350 mm

model

linear storage metres

emvz6-22

36

emvz6-32

48

emvz6-42

60

emvz6-52

72

price in €

All other operating modes, interior fittings options and installation on request.
N.B.: installation lengths incl. a min. operator aisle of 750mm.