

Model

POWER TOWER NANO

LOW-LEVEL ACCESS



The ultimate in Low-Level Powered Access

Push into position, step in, press a button.

Simple. Safe. Efficient.

At JLG we believe safety is paramount. In line with the JLG range, the Power Tower Nano has Auto-Lok wheels on elevation, as standard.

With a 2.5 m platform height and 4.5 m working height, the heavy-duty Nano maximises platform size whilst minimising working footprint, giving the operator more room to work in confined areas.

Typical applications and users: Nano maximizes platform size within a small footprint, ideal for users where the workspace is congested; second fix M&E work, busy retail refitting, simple spot work, new construction or maintenance.

Key Features

- 4.5 m working height
- Low platform entry height only 360mm
- Only 1.19 x 0.75 m working footprint
- Passes easily through single doorways
- Large 1.0 x 0.73 m platform size, gives the user more room to work
- Heavy duty Auto-Lok wheels on elevation

PUSH AROUND

Indoor use*

Working Height: 4.5 m

Applications: 2nd Fix. Spot Work. Pipe & Ductwork. M&E. Shopfitting. Retail.



Largest platform size in class;
small working footprint.

Model POWER TOWER NANO

LOW-LEVEL ACCESS

Specifications

OPERATING DIMENSIONS

working height:	4.50 m
Maximum platform height:	2.50 m
Closed platform height:	0.36 m
Platform dimensions:	1.00 m x 0.73 m
Working footprint:	1.19 m x 0.75 m
Safe working load:	200 kg (1 person plus tools)

CLOSED DIMENSIONS

Length:	1.195 m
Width:	0.75 m
Height:	1.56 m
Weight:	285 kg

POWER OPTIONS

Power:	12V D.C. Battery.
Controls:	Simple push button heavy duty pendant controls for ground and platform.
Construction:	Heavy duty fabricated steel superstructure and 2 stage mast with Ultra-Glide technology. Tough, powder coated finish.
Safety:	Full fail-safe hydraulic circuit. Auto-Lok wheels.
Options:	Tilt alarm with auto cut-out. Protective storage cover.

Safety features

- Hydraulic circuit complete with check valve on lift cylinder
- Improved heavy-duty Auto-Lok wheels on elevation provide secure base
- Emergency descent from ground level
- Audible ascent and descent drive alarm



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hooftdorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 3750
www.jlg.com

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

An Oshkosh Corporation Company