CT40

Mobile Computer

Today's retailers need mobile devices that can help them deliver a consistent, high-quality experience across channels to their customers. Ideally, they want a single device that can handle it all – from order picking at the distribution center to in-store merchandising and home delivery.

Introducing the Honeywell CT40 mobile computer. Designed for retail store associates and other highly mobile workers, the lightweight, ergonomic CT40 is a sleek and stylish enterprise-class, full-touch device that helps improve worker productivity and minimize fatigue. Equipped with a high-performance octa-core chipset, fast Wi-Fi, and 4G LTE connectivity, the CT40 mobile computer gives associates quick access to business-critical information whenever they need it. The CT40 device is built tough with a rugged housing and Corning® Gorilla® Glass 5 screen to protect the unit against drops and falls.

Built on Honeywell's Mobility Edge™ platform, the CT40 mobile computer is upgradable across five generations of Android™, providing a lower overall TCO and maximizing return on customer investment. And it's validated by Android Enterprise Recommended, a Google-led initiative that helps businesses confidently select, deploy, and manage the Android devices and services best suited to their enterprise needs.

Compatible with a broad range of Honeywell connected applications, third-party software, and a comprehensive portfolio of accessories, the CT40 mobile computer is more than just a hardware device. It's a highly integrated solution for retail and light-duty field mobility environments – from the shop floor and the backroom indoors to light-duty logistics and delivery outdoors.







reddot award 2019



Built on the future-proof Mobility Edge platform, the sleek and versatile CT40 mobile computer enables retail associates and highly mobile workers to increase productivity and deliver a seamless customer experience throughout the day.

FEATURES AND BENEFITS



The Mobility Edge enterprise management tools allow companies to test and validate applications once, accelerate deployments across the enterprise, optimize device performance, simplify maintenance, and extend product lifecycle.



Future-proof investment protection with support for five Android generations, starting with Android 7.1 (N). Security updates available for up to five years past the last Google patch through Honeywell Sentinel.



Easy compatibility and seamless integration with both Honeywell Connected applications as well as third-party applications such as MDM, Push to Talk, and VoIP software to maximize efficiency and protect your investment.



The rugged, sleek CT40 device is ergonomic, lightweight, and simple to use, fitting easily in the hand and able to be used comfortably and productively all day long.



Three scan imager options offered for enhanced data capture speed and reading range, even outdoors; choose user-friendly green LED dot or sharp red frame laser aimer.



CT40 Technical Specifications

MECHANICAL

 $\textbf{Dimensions:}\ 162\ \text{mm}\ \text{x}\ 77\ \text{mm}\ \text{x}\ 18.2\ \text{mm}$

 $(6.4 \text{ in } \times 3.0 \text{ in } \times 0.7 \text{ in})$

Weight: 289 g (10.1 oz) with battery pack **Display Size:** 12.7 cm (5.0 in) TFT **Resolution:** High Definition (1280 x 720)

Backlight: LED

Touchscreen: Multi-touch capacitive, Gorilla

Glass 5

Hard Keys: Volume up/down key, left/right scan,

power button

Soft Key: On-screen scan button, reprogrammable into an application quick-

laurierrkey

Audio: 3.5 mm jack**, PTT, VoIP ready, speaker,

HAC-compliant

I/O Ports: Durable, custom IO connector

ENVIRONMENTAL

Operating Temperature: -20° C to $+50^{\circ}$ C $(-4^{\circ}$ F to $+122^{\circ}$ F)

Storage Temperature: -30° C to $+70^{\circ}$ C (-22° F to $+158^{\circ}$ F)

Humidity: 5% to 95% (non-condensing)

Drop: Multiple 1.2 m (4 ft) drops to concrete at -10° C to $+50^{\circ}$ C ($+14^{\circ}$ F to $+122^{\circ}$ F). Multiple drops from 1.8 m (6 ft) to concrete per MIL-STD-810G with rubber boot

Tumble: 1,000 times at 0.5 m (1.6 ft)

ESD: ±8 kV direct; ±12 kV air

Environmental Sealing: Independently certified to meet IP64 standards for moisture and particle intrusion

SYSTEM ARCHITECTURE

Processor: 2.2 GHz Qualcomm® Snapdragon™

660 octo-core

Memory: 2 GB or 4 GB DDR4 RAM, 32 GB Flash

Operating System: Each Android version

guaranteed from 7.1 to at least 11/R, committed support for Android 12 and 13 pending feasibility

Default Language: World Wide English

Storage Expansion: User-accessible microSD card up to 512 GB (SDXC/SDHC/SDIO-compliant)

Battery: Li-lon, 3.85 V, 4020 mAh; smart battery with integrated diagnostic tools

Hours of Operation: 12+ hours

Scan Engine: Honeywell N3601, N6603, N6703, S0703 and FlexRange Slim Imager (1D/2D barcode symbologies), Honeywell SDKs for Android

Application Software: Honeywell utilities and

105

Camera: 13-megapixel color camera with

autofocus

Sensor: Ambient light sensor, proximity sensor,

accelerometer, gyroscope

WARRANTY

One-year factory warranty

WIRELESS CONNECTIVITY

WWAN: WWAN Radio (ATT/VZW/SPRINT/TMO/NA/EU)

LTE Advanced Support

Up to 400 Mbps CAT13 LTE downlink
Up to 75 Mbps CAT5 LTE uplink
LTE (FDD) – Bands 1, 2, 3, 4, 5, 7, 8, 12,
13,17, 19, 20, 25, 26, 28, 29
LTE (TDD) – Bands 38, 39, 40, 41
UMTS/HSPA+ (3G) – Bands 1, 2, 4, 5, 6, 8, 9, 19
GSM/GPRS/EDGE Quad-Band
(850/900/1800/1900 MHz)
1xRTT/EV-DO – Bands BCO, BC1, BC10

WLAN: IEEE 802.11 a/b/g/n/ac; Wi-Fi certified Additional WLAN Features: 802.11 d/e/h/i/k/

WLAN Security: OPEN, WEP, WPA/WPA2

(Personal and Enterprise)

Supported EAP: TLS, PEAP, TTLS, PWD, FAST,

LEAP CCX Version 4 certified

Bluetooth®: V5.0 Bluetooth and BLE Supported **Bluetooth Profiles:** HFP, PBAP, A2DP, AVRCP,

OPP, SPP, GATT

(B26BW)

NFC: Integrated Near Field Communication

VPN: IPSec V4/L2TP, PPTP
Push to Talk (PTT): Supported

GPS Supported Protocols: Simultaneous GNSS Receiver Support for GPS, GLONASS, Galileo,

and Beidou

* Specifications are subject to change without notice.

** 3.5mm jack is available on Wi-Fi version only.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Mobility Edge is a trademark or registered trademark of Honeywell International Inc. in the United States and/or other countries.

Android is a trademark or registered trademark of Google Inc. in the United States and/or other countries.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated in the United States and/or other countries.

Corning and Gorilla Glass are trademarks or registered trademarks of Corning, Inc. in the United States and/or other countries.

Bluetooth is a trademark or registered trademark of Bluetooth SIG, Inc. in the United States and/or other countries.

CAUTION

ASSER RADIATION

ASSER RADIATION

DO NOT STARE INTO BEAM

CLASS 2 LASER PRODUCT.

RAYONNEMEMT LASER

NE PAS REGARDER DANS

NE PAS REGARDER DANS

LE FAISCEAU. APPAREIL

A LASER DE CLASSE 2

MR 58-860m Pube durato 18-80m

COMPLET AND 12 CPR 1149, 92 and

(4) 1 except foreigne pursuant laser Moton No. 50. Oalet Java 24 2007

董針光、前功 直要范末中

之报题基督品

CAUTION 小 心 LASER RADIATION DO NOT STARE INTO BEAM CLASS 2 LASER PRODUCT. 1mW. 630-680nm. Pulse duration 16.8ms IEC 60825-1:2007 and IEC 60825-1:207 and iEC 60825-1:207 素先・前身直視惑光束 文表意产品





For more information

www.sps.honeywell.com

Honeywell Safety and Productivity Solutions

855 S Mint Street, Charlotte, NC 28202 800-582-4263 www.honeywell.com

