BKG[®] Master-LineTM Underwater Pelletizing System

Throughput range up to 2,000 kg/hr (4,400 lb/hr)

Processes:

- Masterbatch
- Compounding
- Recycling

Materials:

 All materials which behave like thermoplastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)



Features:

- Modular design
- Completely skid-mounted
- Dual door dryer access for easy cleaning
- Robust design and equipped with all the essentials

Benefits:

- Our entry-level underwater pelletizing system
- Compact footprint
- Flexibility for material and / or color changes
- Easy and fast cleaning of the system components
- Easy operation, simple handling

Model	Pellet Dryer	Capacity
Master-Line™ 300	TVE 1001 ED	< 500 kg/hr (1,100 lb/hr)
Master-Line™ 1000	TVE 1001 ED	< 1,200 kg/hr (2,600 lb/hr)
Master-Line [™] 2000	TVE 2000 ED	< 2,000 kg/hr (4,400 lb/hr)

Nordson BKG GmbH Hessenweg 3 48157 Münster / Germany +49.251.26501.0 Phone USA +1.828.326.9888 Phone China +86.21.5785.091.8 Phone

