

# BKG<sup>®</sup> Optigon<sup>™</sup>

## Underwater Pelletizing System

**Throughput range up to 15,000 kg/hr (33,000 lb/hr)**

### Processes:

- Polymerization
- Masterbatch
- Compounding
- Recycling

### Materials:

- All materials which behave like thermo-plastic polymers (PE, PP, PS, ABS, SAN, PA, PET, PC, POM, TPE, TPU, EVA, APAO, PBT, PMMA, EPDM)
- Highly-filled compounds
- Materials which generate a high degree of fines



### Features:

- Polygon<sup>™</sup> automatic filter + secondary filtration
- Self-cleaning tempered water system
- Modular design
- Completely skid-mounted
- Noise reduction of the pellet dryer ≤ 80 dB(A)
- Large dryer door for easy access
- Pre-dewatering
- Dryer available with inspection window and lights
- Cleaning system for the pellet dryer available
- Larger systems upon request

### Benefits:

- Continuous, automatic water filtration
- High level of automation, reduced operator intervention
- Improved water filtration level (up to 70µm)
- Optional belt filter maximizes system automation
- Energy savings during operation through elimination of secondary pump
- Premium options / features available
- Process water tank can be heated via steam or other medium versus electrical heating
- Explosion protected design according to ATEX available

Model	Pellet Dryer	Capacity
Optigon <sup>™</sup> 2	TVE 2004 SR	< 2,500 kg/hr (5,500 lb/hr)
Optigon <sup>™</sup> 3	TVE 6002 SR	< 5,000 kg/hr (11,000 lb/hr)
Optigon <sup>™</sup> 4	TVE 6002 SR	< 7,500 kg/hr (16,500 lb/hr)
Optigon <sup>™</sup> 5	TVE 12000 SR	< 15,000 kg/hr (33,000 lb/hr)

**Nordson BKG GmbH**  
Hessenweg 3  
48157 Münster / Germany  
+49.251.26501.0 **Phone**

**USA**  
+1.828.326.9888 **Phone**

**China**  
+86.21.5785.091.8 **Phone**

www.nordsonpolymerprocessing.com | info@nordsonpolymerprocessing.com  
© 2015 Nordson BKG GmbH  
Printed in USA  
8/2016

