

# THEMIS

## TI-1010 / TI-1010A

### THE SMART MULTI-PURPOSE INFORMATION TERMINAL



The Themis Info Terminals TI-1010 and TI-1010A have a lot to offer with a wide range of functionalities. Obtaining information or self-service become more and more important to improve customer service. Whether users want to check product prices, product variations, special offers or whatever kind of information might be needed, the TI-1010 and TI-1010A is the best choice. Customers can choose between the Intel powered TI-1010 with Windows 10 or its Rockchip companion TI-1010A running with Android 8.1. With the 10.1 inch wide screen touch display and optional peripherals like 2D scanner and RFID / NFC reader the terminal can also be used as a price checker, information terminal, ordering terminal or as an access control device. The integrated Power over Ethernet (PoE+) capability make installations very easy.

#### SPECIAL FEATURES

- All-in-one information terminal with 10.1" wide screen LCD
- 10-point PCAP touch
- Windows 10 or Android 8.1
- Fanless design
- Integrated Power over Ethernet (PoE+)
- 2D scanner

#### OPTIONAL

- Intel® Celeron® J1900 for Windows 10
- Rockchip RK3288 for Android 8.1
- RFID/NFC reader

## TI-1010 / TI-1010A

Model		TI-1010	TI-1010A
Display	Max Resolution	1280 x 800	
	Size	10.1"	
	Brightness	280 nits	
	Contrast	600:1	
	Response Time	10ms	
	Viewing Angle	Right 75° Left 75° / Upper 75° Lower 75°	
	Technology	LCD with LED backlight	
	Touch	10-point PCAP touch	
System	CPU (fanless)	Intel® Celeron® J1900 (Bay Trail) 2,00 GHz up to 2,40 GHz, Quad-core	Rockchip RK3288 Quad-core Cortex-A17 up to 1.8 GHz
	RAM	1 x 4GB DDR3L 1333MHz SO-DIMM	2GB DDR3
	Storage	1 x 120GB mSATA SSD	16GB eMMC Flash
	OS	Windows 10 Enterprise LTSC or SAC	Android 8.1 (support Google Play Services)
	I/O Interface		
	DC in	1 x DC 12V input power-jack	1 x DC 12V input power-jack
	LAN	1 x RJ45	1 x RJ45
	USB	2 x USB 2.0	2 x USB 2.0
	TF card	-	1 x
	Reset Button	via SIM tool	via SIM tool
	Power On	via SIM tool	via SIM tool

\* Specification is subject of change without prior notice Aug20

## TI-1010 / TI-1010A

Model	TI-1010		TI-1010A
Other	Color	black	
	VESA Mounting	75 x 75	
	Material	Plastic with aluminum back housing with top flat panel glass	
	Speaker	1 x 3 Watts	
Power	Power	AC-In 100~240V / DC-Out 12V/5A	AC-In 100~240V / DC-Out 12V/2A
	Power over Ethernet	supports PoE+ (802.3at)	
	Dimensions without mounting	275.46 mm (W) x 234.96 mm (H) x 68,03 mm (D)	
Weight	without mounting	1.84 kg	
Environment	Operating Temperature	0°C ~ 50°C	
	Storage Temperature	-20°C ~ 60°C	
Scanner	2D scanner	supports all common 1D/2D barcodes	
Options	NFC/RFID reader	supports LF and HF (125 kHz, 134.2 kHz and 13.56 MHz), supports all major transponders and ISO standards like ISO14443A/B (T=CL), ISO15693, ISO18092 / ECMA-340 (NFC)	

\* Specification is subject of change without prior notice Aug20