

# THEMIS

---

## ARGO

### RELIABLE COMPACT BOX PC



Argo is a compact Box PC for a variety of applications like POS and Digital Signage or it can be simply used as a Desktop PC. It is running completely fanless with either Intel's Quad Core Celeron J1900, Intel's 6th Generation Dual Core i3-6100U or i5-6200U. With its dust proof and robust design Argo is a performant high reliability BOX PC for everyday use. The operation of two displays running independently are supported with its VGA and HDMI output, whereas the Core-i3 and Core-i5 version also support video output in 4K resolution. All four serial ports can be optional powered with 5 or 12V with easy jumper settings behind the front cover. The hard drive can be swapped very easily from the front for easy maintenance.

---

#### Special Features

Intel®Celeron®J1900, Intel®Core™ i3-6100U or Intel® Core™ Prozessor i5-6200U

Windows 10 IoT

Aluminum casing

Dust proof and fanless design

Swappable storage design

Support VESA Mount

---

#### Optional

Windows POSReady 7

## Argo

Modell		TB-801B	TB-801S -I3	TB-801S-I5
Processor	CPU	Intel® Celeron® J1900 (Bay Trail) 2.00 GHz up to 2.40 GHz, Quad Core	Intel® Core™ i3-6100U (Skylake), 2.30 GHz, dual core, 3MB SmartCache	Intel® Core™ Prozessor i5-6200U (Skylake), 2.30 GHz up to 2.80 GHz, dual core 3MB SmartCache
Memory	Technology	Dual-channel DDR3L		
	Capacity	4 GB (optional 8 GB)		
	Socket	1 x 204-pin SO-DIMMs		
Storage	Type	120 GB SATA III SSD		
Operating System	Support	POSReady 7, Windows 10 IoT		
Display Support	Controller	Intel® HD Graphics	Intel® HD-Graphics 520	Intel® HD-Graphics 520
	Graphic Memory	Shared Video RAM	Shared Video RAM	Shared Video RAM
	Max. Resolution	1920 x 1200	4096 x 2304	4096 x 2304
	USB 2.0	3 x rear, 2 x front	2 x rear, 2 x front	2 x rear, 2 x front
	USB 3.0	1 x rear	2 x rear	2 x rear
	VGA		1 x	
	HDMI		1 x	
	Ethernet	1 x (Realtek PCIe NIC RTL8111F for 1000Mbps)		
	Audio Line-out		1 x	
	Mic In		1 x	
	Serial COM	4 x DB9 0/5/12V configurable at front panel		
	PS/2		1 x	
	Mini PCI		2 x internal	
	Power Supply	100 - 220V; 50-60 Hz		
	DC out	12A 5A		
Others	Dimension	215 mm (W) x 233 mm (H) x 65 mm (D)		
	Weight	2 kg		
	Material	ABS Plastic, Metal Plate		
	Color	black		
	VESA	yes		
Environment	Operating Temperature	0°C ~ 60°C		
	Storage Temperature	20°C ~ 75°C		
	Operating Humidity	10% ~ 80%, non-condensing		
	Storage Humidity	10% ~ 80%, non-condensing		

\* Specification is subject of change without prior notice. Jul19



EUROPE	+49 40 450 635-0	info@partner-tech.eu
UNITED KINGDOM	+44 1928 579 707	sales-uk@partner-tech.eu
IBERIA	+34 913 120632	comercial@partner-tech.eu
ADRIA	+386 1 566 25 20	prodaja@partner-tech.eu