## PTFE smooth hose system



Product name	marsoflex® PTFE smooth hose system     Type G, GA and GC
Description	Our marsoflex PTFE smooth hose is the result of the consistent further development of the PTFE corrugated tube hose. Its smooth hose tube ensures a particularly low level of flow resistance and makes cleaning very easy.
Properties	Phthalate-free, tested according to 1907/2006/ EC (REACH). Complies with USP XXXVI class VI, not cytotoxic according to ISO 10993 Section 5:2009. Suction and pressure hose (675 mmHg)
Hose tube	PTFE (polytetrafluorethylene) white, smooth, also available in black (conductive), phthalate-free, tested according to 1907/2006/ EC (REACH). It complies with FDA 21 CFR 177.1550, USP XXXVI class VI, ISO 10993 sections 5,10, 11:2009, regulation (EU) no. 1935/2004 and (EU) no. 10/2011, 3A Sanitary Standard Class II
Reinforcement	Stainless steel braiding, stainless steel spiral
Hose cover	Silicone, smooth, white. Corresponds to FDA CFR 21 177.2600, BfR recommendation XV, European Regulation 1935/2001/EC. Resistant to heat, abrasion, ageing and ozone, here B1SIL as an example.
Application temperature	-60 $^{\circ}$ C/+260 $^{\circ}$ C (-76 $^{\circ}$ F/+500 $^{\circ}$ F); the operating temperature of the hose directly depends on the medium to be transported and the contact period.
Special version	Proof of suitability for the highest requirements for cleanliness - extractables study -

