



RF WS WME01

Wireless Volatage Meter 0-1V DC Sensor



Product name	RF WS WME01
Voltage Meter Specifications	
Accuracy	+/- 3% FS
User Calibrated Accuracy	+/- 0.5% FS
Maximum Rated Input Voltage	20 Volts DC
Resolution	~5 mV
Voltage Range	0 – 10 Volts DC
Open Circuit Voltage	~1.880 Volts
868 MHz Specifications	
Operating Frequency	868 MHz Operating Frequency
Certifications	CE Certified and Complies with CISPR 22:2008-09 / EN 55022:201 Class B and ETSI EN 300 220-2 V2.4.1 (2012-05)
Coin Cell Specifications	
Battery Type	Replaceable 3.0V Coin Cell Battery
Dimension	1.775 in x 1.04 in x 0.785 in
Max Operating Temperature	-20°C to +60°C (-4° to +140°F)
Optimal Battery Operating Temperature (Coin Cell)	+10°C to +50°C (+50°F to +122°F)
Supply Voltage	2.0 - 3.6 V (Single CR2032 Coin Cell Battery)
Device Range	250 - 300 ft. non-line-of-sight device range*
Battery Life	At 1 hour heartbeat setting, coin cell battery will typically last ~ 1-2 Years. **
Enclosure Material	ABS
Dimensions	Height: 0.785 in (19.939 mm)
Articel No:	RF WS WME01
Typical Applications:	
Charging Battery Monitoring	Machinery
Voltage Measurement	Electrical Motors
Transducer Measurement	Electrical Vehicles Health



Contact:

sales@radioforce.net www.radioforce.net