CL-SERIES

High quality ultrasonic cleaner with a high ultrasonic effect for reliable parts cleaning every day. Suitable for many tasks.

Analogue display

- Setting of time 0-60 min.
- Setting of temperature 0-80°C
- Standard frequency 40 khz.

Digital multifunction display

- Setting of time and temperature
- Powerfunction setting of frequency and watt-usage
- Multifrequency, Choose between 21,5 or 40 khz.

Available options:

- Stainless steel baskets
- Basket covers
- Fixtures
- Weekly timer.



MODEL	CL100	CL150	CL300	CL600
Volume	4,0 L	5,7 L	16 L	25 L
Tank size (LxWxH)	245x135x140 mm	300x140x140 mm	325x300x190 mm	500x300x190 mm
Basket size	190x100x120 mm	245x110x120 mm	250x245x150 mm	450x250x150 mm
Outside dimensions	300x170x300 mm	370x180x300 mm	420x330x420 mm	600x330x420 mm
Ultrasonic effect	160W	240W	320W	640W
Frequency	21,5 / 40 Khz			
Temperature	0-80°C	0-80°C	0-80°C	0-80°C
Power supply	220/240V, 50 hz.	220/240V, 50 hz.	220/240V, 50 hz.	220/240V, 50 hz.





solution for smaller workshops, laboratories, dental clinics etc.

√ Digital multifunctional display or analog control

The ultrasonic cleaner has a digital display with frequency, watt, temperature and time settings, or alternatively the more simple analog control panel.

√ Stainless steel construction

The ultrasonic cleaner is constructed with a stainless steel tank, cabinet and tank cover.

√ Including basket and lid

The ultrasonic cleaner comes with a basket and lid as standard.

√ Bottom valve

Bottom valve in brass for easy emptying of the tank. Not available for CL 100.