

# ERGOBJÖRN SPECIAL TRUCKS



## TERMS & FUNCTIONS

Despite our wide standard range of trucks and trolleys, customers sometimes still need tailor-made solutions. That's no problem for us. One of the secrets behind Helge Nyberg's success is that we have the resources and organisation to deve-

lop products and solutions according to customers' specific requirements. Always available to our customers, we have experienced product developers with knowledge and competence concerning logistics and material handling.

# HelgeNyberg

THE PRODUCER OF ERGOBJÖRN



## TOWING TRACTOR 728

A stable towing truck that is add-on and flexible with our modular system. Here with a shelf rack, which is suitable for a computer and printer for example.

Tow truck with an integrated platform. It is also available with a platform without shelf. The shelves are module-based, which makes it easy to adapt them according to your need.

### Dimensions and technical data

<b>Art No</b>	14 90 25 55
<b>Max. speed</b>	12 km/h
<b>Max. towing capacity</b>	1000 kg
<b>Max. gradient</b>	10%
<b>Length</b>	1950 mm
<b>Width</b>	975 mm
<b>Height</b>	1200 mm
<b>Instegshöjd</b>	72 mm
<b>Ground clearance</b>	32 mm
<b>Axle distance</b>	1180 mm
<b>Drive wheels</b>	250x80 mm
<b>Rear wheels</b>	100x45 mm
<b>Support wheels</b>	80x35 mm
<b>Electrical system</b>	24 V (AC)
<b>Power output</b>	1000 W



## MULTITRUCK

At the hospital where this truck solution has been tried out, they have between 6500 and 7000 bed transports every month. The transport frequency is high and besides handling the transfer of patients between departments, the beds shall also pass through the laundry and bed central to be made.

The truck has contributed to a greater efficiency and a significantly improved ergonomic situation for all personnel handling bed transports. The truck can handle many different types of beds and can also be used in elevators.

### Dimensions and technical data

<b>Art No</b>	14 90 26 14
<b>Max. speed</b>	12 km/h
<b>Max. towing capacity</b>	500 kg
<b>Max. gradient</b>	10%
<b>Width</b>	1120 mm
<b>Height</b>	1100 mm
<b>Threshold height</b>	91 mm
<b>Ground clearance</b>	32 mm
<b>Axle distance</b>	1000 mm
<b>Drive wheels</b>	250x80 mm
<b>Rear wheels</b>	200x50 mm
<b>Support wheels</b>	80x35 mm
<b>Electrical system</b>	24 V (AC)
<b>Power output</b>	1000 W



## TOWING TRACTOR 714

The integrated platform is suitable for smart transportation of for example roll containers. It is also possible to connect additional trolleys or taxi trolleys for towing.

### Dimensions and technical data

<b>Art No</b>	14 90 24 74
<b>Max. speed</b>	12 km/h
<b>Max. towing capacity</b>	300 kg
<b>Max. gradient</b>	5-10%
<b>Length</b>	1955 mm
<b>Width</b>	975 mm
<b>Height</b>	1202 mm
<b>Threshold height</b>	70 mm
<b>Ground clearance</b>	30 mm
<b>Axle distance</b>	1180 mm
<b>Drive wheels</b>	250x80 mm
<b>Rear wheels</b>	200x50 mm
<b>Support wheels</b>	80x35 mm
<b>Electrical system</b>	24 V (AC)
<b>Power output</b>	1000 W

# HelgeNyberg

**HEAD OFFICE / SWEDEN**  
Industrivägen 2  
SE-523 90 Ulricehamn

Phone +46 321 263 00

info@helge-nyberg.com  
www.helge-nyberg.com

**SALES OFFICE / GERMANY**  
Contact information:  
www.helge-nyberg.com