ERGOBJÖRN STEP TROLLEY





TERMS & FUNCTIONS

Trolley with steps for picking and replenishment in warehouse and production facilities. The combined solution provides an efficient mobile workplace, facilitating order picking up to a height of 3 metres.



the producer of Ergobjörn





STEP TROLLEY

Trolley with steps for picking and replenishment in warehouse and production facilities. The combined solution provides an efficient mobile workplace, facilitating order picking up to a height of 3 metres.

The uprights are held together by a top element. The lower shelf is recessed in the frame profile. Fixed distance between shelves: 485 mm for 3-shelf trolley, 305

mm for 4-shelf trolley.

Max. load 500 kg. Max. load, shelves: 150 kg. Max. load, product resting shelf: 40 kg.

Two fixed docking wheels with tugs and two swivel wheels with grey elastic rubber tyres measuring 200x50 mm, ball bearing hubs.

3 shelves								
Art. no.	Shelves	Lower shelf	Mid shelf	Upper shelf	Length	Width	Height	
15272695	3	1200x600	1064x600	914x600	1250	650	2230	
4 chalves)
4 shelves Art. no.	Shelves	Lower shelf	Mid shelf 1	Mid shelf 2	Upper sh	elf Lei	ngth ∣ Wic) Ith ∣ Heig



HEAD OFFICE / SWEDEN Industrivägen 2 SE-523 90 Ulricehamn

Phone +46 321 263 00 Fax +46 321 263 01 info@helge-nyberg.com www.helge-nyberg.com **SALES OFFICE / GERMANY** Contact information: www.helge-nyberg.de