

Product Information

TYPO

Design Gerd Rausch



TYPO | Model 1140 - Model 1170

Looking for something else than chairs? TYPO offers the solution with bench systems combining esthetics and utility.

Areas of use

LOBBIES + WAITING AREAS | MULTIFUNCTIONAL USE |

The TYPO meets a wide range of technical requirements and blends in perfectly with any architectural environment.

Frame

T-shaped side sections made from Ø 40 x 2 mm tube steels, connected by soldering, welded together with the 60 x 30 x 2 mm oval tube crossbeam. The welded connection has been covered with black plastic caps.

Frame surfaces

Standard version of the side sections, side bars and crossbeam: powder-coated in black, optionally powder-coated according to the BRUNE® collection.

Seat and back support

Ergonomically shaped perforated sheet metal (approx. 2 mm thick). Perforation pattern: 3 mm Ø spaced in distances of 6 mm. The perforated rows are offset diagonally. Seats and back supports are welded to the frame at the side brackets (concealed welding joints). Side brackets made from 22 x 2 mm tubular steel tubes. Seat screwed to the transversal beam with a u-shaped fastening clip.

Upholstery

Seat and back padding for seats in perforated steel, fabric cover according to the BRUNE® collection, fabric categories 3, 4, 6, 7 or 8.

Seat cushion foam: SG/CH 35/50 approx. 25 mm thick

Back cushion foam: SG/CH 35/50 approx. 15 mm thick

SG = specific gravity, weight per m³. CH = compression hardness (e.g.: 50 approx. 50 g/cm² at a compression level of 40 %)

Table top


Table top 45 x 45 cm. Models with a top section made from perforated sheet metal: perforated steel plate. Models with a top section made from plywood and upholstery: plastic plate. Plastic surfaces with plastic edges according to the BRUNE® collection. Plastic plates with rounded edges R 50.

Gliders

Standard version: plastic gliders
 Optionally: with drill holes for fixed attachment to the ground

Dimensions 1140 - 1150 | 1160 – 1170

| | | |
|-------------|----------------------|--|
| Dimensions: | B 114 cm (1140+1160) | 2-seater bench or 1-seater bench + table |
| | B 169 cm (1145+1165) | 3-seater bench or 2-seater bench + table |
| | B 224 cm (1150+1170) | 4-seater bench or 3-seater bench + table |
| | T 62 cm | |
| | H 79 cm | |
| SH 44 cm | | |
| Weights: | 22 kg (1140+1160) | 2-seater bench or 1-seater bench + table |
| | 30 kg (1145+1165) | 3-seater bench or 2-seater bench + table |
| | 38 kg (1150+1170) | 4-seater bench or 3-seater bench + table |



Certificates



TÜV Certificate



Quality management in accordance with
DIN EN ISO 9001



Environmental management system in accordance with
DIN EN ISO 14001